

# TOYOTA 200 SERIES 3800KG GVM UPGRADE

Kit #: TOYKIT067-GVM-D



Capacities	Lovells	OE
GVM	3800kg	3350kg
GCM	7300kg	6800kg
Front Axle	1800kg	
Rear Axle	2000kg	
Towing	3500kg	3500kg

DATES
All models Petrol & Diesel 11/2007 - 2022

SPRING OPTIONS	
FRONT:	TFR-121 – Minimal or no load bearing front accessories. TFR-123 – Light Load bearing front accessories, Alloy Bullbar. TFR-123HD – Heavy Load bearing front accessories, Steel Bullbar, Winch.
REAR:	TRR-122HD – Minimal load bearing rear accessories. Axle capacities under 1600kg TRR-122HDAV – Heavy load bearing rear accessories. Axle capacities over 1600kg

SHOCK PART NUMBERS	
FRONT:	64611007 (Twin Tube Shocks)
REAR:	64611008 (Twin Tube Shocks)

OTHER KIT COMPONENTS
Decals Tyre Placard

NOTES:
<b>SVI Plate Location:</b> Drivers Side Lower B Pillar
<b>Lovells Approval Number:</b> VTA 040257 VTA 046734 (BTC)
<b>Tyres:</b> Factory tyres meet minimum specification
<b>Special Requirements:</b>

TYRE – LOADING INFORMATION				
	FRONT AXLE		REAR AXLE	
TYRE SIZE (minimum) <small>(Tyre Load Index minimum)</small>	285/65 R17 <small>(116)</small>	285/60 R18 <small>(116)</small>	285/65 R17 <small>(116)</small>	285/60 R18 <small>(116)</small>
RIM SIZE (minimum)	17X8J	18X8J	17X8J	18X8J
RECOMMENDED COLD TYRE INFLATION PRESSURE	230kPa <small>(230kPa)</small>	230kPa <small>(230kPa)</small>	230kPa <small>(230kPa)</small>	230kPa <small>(230kPa)</small>
- At maximum GVM				
- (No Load)				
LOAD CARRYING CAPACITY PER AXLE <small>(maximum)</small>	1800kg		2000kg	
<small>( ): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE. THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q" (160km/h). SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 250KG THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3800kg</small>				
<small>LS-LC200 V4 3800</small>				

# TOYOTA 200 SERIES 4000KG GVM UPGRADE

Kit #: TOYKIT081-GVM



Capacities	Lovells	OE
GVM	4000kg	3350kg
GCM	7500kg	6800kg
Front Axle	1900kg	
Rear Axle	2100kg	
Towing	3500kg	3500kg

DATES
All models Petrol & Diesel 11/2007 - 2022

SPRING OPTIONS	
FRONT:	TFR-121 – Minimal or no load bearing front accessories. TFR-123 – Light Load bearing front accessories, Alloy Bullbar. TFR-123HD – Heavy Load bearing front accessories, Steel Bullbar, Winch.
REAR:	TRR-122HD – Minimal load bearing rear accessories. Axle capacities under 1600kg TRR-122HDAV – Heavy load bearing rear accessories. Axle capacities over 1600kg

SHOCK PART NUMBERS	
FRONT:	64611007-46MONO (Mono Tube Shocks)
REAR:	64611008-46MONO (Mono Tube Shocks)

OTHER KIT COMPONENTS
Decals Tyre Placard

NOTES:
<b>SVI Plate Location:</b> Drivers Side Lower B Pillar
<b>Lovells Approval Number:</b> VTA 040257 VTA 046734 (BTC)
<b>Tyres:</b> Factory tyres meet minimum specification
<b>Special Requirements:</b>

TYRE – LOADING INFORMATION				
	FRONT AXLE		REAR AXLE	
TYRE SIZE (minimum) <small>(Tyre Load Index minimum)</small>	285/65 R17 <b>(116)</b>	285/60 R18 <b>(116)</b>	285/65 R17 <b>(116)</b>	285/60 R18 <b>(116)</b>
RIM SIZE (minimum)	17X8J	18X8J	17X8J	18X8J
RECOMMENDED COLD TYRE INFLATION PRESSURE	230kPa (230kPa)	230kPa (230kPa)	240kPa (230kPa)	240kPa (230kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1900kg		2100kg	
<small>( ) : TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE. THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "P" (150km/h). SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 300KG THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE. THE GVM OF THIS VEHICLE MUST NOT EXCEED 4000kg</small>				
LS-LC200 V3 4000				

# TOYOTA 200 SERIES 4200KG GVM UPGRADE

**Kit #: TOYKIT083-GVM-PLAT**



Capacities	Lovells	OE
GVM	4200kg	3350kg
GCM	7700kg	6800kg
Front Axle	1960kg	
Rear Axle	2340kg	
Towing	3500kg	3500kg

DATES
All models Diesel Only 11/2007 - 2022

SPRING OPTIONS	
FRONT:	TFR-121 – Minimal or no load bearing front accessories. TFR-123 – Light Load bearing front accessories, Alloy Bullbar. TFR-123HD – Heavy Load bearing front accessories, Steel Bullbar, Winch.
REAR:	TRR-122HD – Minimal load bearing rear accessories. Axle capacities under 1600kg TRR-122HDAV – Heavy load bearing rear accessories. Axle capacities over 1600kg

SHOCK PART NUMBERS	
FRONT:	64611007S-2.0ADJMONO (Remote Res Shocks)
REAR:	64611008S-2.0ADJMONO (Remote Res Shocks)

OTHER KIT COMPONENTS
Cat 6 indicators Decals Tyre Placard

NOTES:
<b>SVI Plate Location:</b> Drivers Side Lower B Pillar
<b>Lovells Approval Number:</b> VTA 050728
<b>Tyres:</b> Factory tyres meet minimum specification
<b>Special Requirements:</b> <b>CAT6 indicators are required to be compliant</b>

TYRE – LOADING INFORMATION				
	FRONT AXLE		REAR AXLE	
TYRE SIZE (minimum) <small>(Tyre Load Index minimum)</small>	285/65 R17 <b>(116)</b>	285/60 R18 <b>(116)</b>	285/65 R17 <b>(116)</b>	285/60 R18 <b>(116)</b>
RIM SIZE (minimum)	17X8J	18X8J	17X8J	18X8J
RECOMMENDED COLD TYRE INFLATION PRESSURE	230kPa	230kPa	240kPa	240kPa
- At maximum GVM	(230kPa)	(230kPa)	(230kPa)	(230kPa)
- (No Load)				
LOAD CARRYING CAPACITY PER AXLE (maximum)	1960kg		2304kg	
<small>( ): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE            THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.            THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "P" (150km/h).            SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION            THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 300KG            THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE. THE GVM OF THIS VEHICLE MUST NOT EXCEED 4200kg</small>				
<small>LS-LC200 V3 4200</small>				

# TOYOTA 200 SERIES 4000KG BTC UPGRADE

Kit #: TOYTOW001-BTC-ST-



Capacities	Lovells	OE
GVM		
GCM	7800kg	6800kg
Front Axle		
Rear Axle		
Towing	4000kg	3500kg

## DATES

All models

Diesel Only

11/2007 - 2022

## STAGE 1 KIT COMPONENTS

Heavy Duty Fabricated Height Adjustable Hitch Tongue (BTCU001-T-1)

Heavy Duty Lovells Haulace All Terrain Hitch (BTCU001-H-2)

1 ¼" Shank Tow Pillar (BTCU001-HP)

Haulace Aero Stainless Steel Handbrake (LHA55601A)

Decals

Fitting Instructions

## STAGE 2 KIT COMPONENTS

1200LB WDH System (BTCU001-T-2)

Heavy Duty Height Adjustable Hitch Shank 95mm (LDH55S01A)

Heavy Duty Height Adjustable Hitch Shank 150mm (LDH55L01A)

Heavy Duty Lovells Haulace All Terrain Hitch (BTCU001-H-2)

1 ¼" Shank Tow Pillar (BTCU001-HP)

Haulace Aero Stainless Steel Handbrake (LHA55601A)

Decals

Fitting Instructions

## NOTES:

**Lovells Approval Number:** VTA 040257 & VTA 046734

Does suit 3800kg, 4000kg & 4200kg GVM Upgrades

**MUST BE DONE IN CONJUNCTION WITH A LOVELLS GVM UPGRADE**

Stage 1: Max Tow ball download – 350kg

Recommended to towing 3500kg to 3700kg Apparatus

Stage 2: Max Tow ball download – 400kg

Recommended to towing 3700kg to 4000kg Apparatus