

MAZDA BT-50 MY12

3500KG GVM UPGRADE



Kit #: FORDKIT009-GVM

Capacities	Lovells	OE
GVM	3500kg	3200kg
GCM	6600kg	6000kg
Front Axle	1580kg	
Rear Axle	2020kg	
Towing	3500kg	3500kg

<u>DATES</u>
All body types 3.2Ltr Engine 01/2012 – 06/2020

<u>SPRING OPTIONS</u>	
FRONT:	FFS-90 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1300kg FFR-90 – Minimal load bearing front accessories, including Bullbar. Axle capacities over 1300kg
REAR:	FR-1XHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

<u>SHOCK PART NUMBERS</u>	
FRONT:	64611037 (Twin Tube Shocks)
REAR:	6462525T (Twin Tube Shocks)

<u>OTHER KIT COMPONENTS</u>
Eye & Shackle Bushes
U-Bolts
Greasable Shackles
Greasable Pins
Tyre Placard
Decals

<u>NOTES:</u>
SVI Plate Location: State Compliance Only
Lovells Approval Number: VTA 047037
Tyres: Factory tyres meet minimum specification
Special Requirements: May require drive shaft spacer

<u>TYRE – LOADING INFORMATION</u>						
	FRONT AXLE			REAR AXLE		
TYRE SIZE <small>(minimum)</small> <small>(Tyre Load Index minimum)</small>	255/70 R16 (110)	265/65 R17 (112)	265/60 R18 (110)	255/70 R16 (110)	265/65 R17 (112)	265/60 R18 (110)
RIM SIZE <small>(minimum)</small>	16X7J	17X7.5J	18X8J	16X7J	17X7.5J	18X8J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	260kPa (240kPa)	260kPa (240kPa)	260kPa (240kPa)	300kPa (240kPa)	300kPa (240kPa)	300kPa (240kPa)
LOAD CARRYING CAPACITY PER AXLE <small>(maximum)</small>	1480kg	1480kg	1480kg	2020kg	2020kg	2020kg
(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE						
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.						
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "N" (140km/h).						
THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG						
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3500kg						

LS-Ford Ranger and Mazda BT50 TP05

Ph: +61 2 9820 6800

Email: sales@lovells.com.au
www.lovellsauto.com.au



MAZDA BT-50 MY12

3500KG GVM UPGRADE

With Cooling Upgrade for Extra GCM



Kit #: FORDKIT0009-GVM-R

Capacities	Lovells	OE
GVM	3500kg	3200kg
GCM	7000kg	6000kg
Front Axle	1480kg	
Rear Axle	2020kg	
Towing	3500kg	3500kg

DATES
All Body types
3.2 Ltr Engine
01/2012 – 06/2020

SPRING OPTIONS

FRONT: FFS-90 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1300kg
 FFR-90 – Minimal load bearing front accessories, including Bullbar. Axle capacities over 1300kg

REAR: FR-1XHD – Only Rear Leaf Spring Available, 400 to 500kg Constant Load

SHOCK PART NUMBERS

FRONT: 64611037 (Twin Tube Shocks)

REAR: 6462525T (Twin Tube Shocks)

OTHER KIT COMPONENTS

Eye & Shackle Bushes Lovells Radiator
 U-Bolts Lovells Intercooler
 Greasable Shackles
 Greasable Pins
 Lovells
 Tyre Placard
 Decals

NOTES:

SVI Plate Location:

State Compliance Only

Lovells Approval Number:

VTA 047037

Tyres:

Factory tyres meet minimum specification

Special Requirements:

May require drive shaft spacer

TYRE – LOADING INFORMATION						
	FRONT AXLE			REAR AXLE		
TYRE SIZE (minimum) <small>(Tyre Load Index minimum)</small>	255/70 R16 <small>(110)</small>	265/65 R17 <small>(112)</small>	265/60 R18 <small>(110)</small>	255/70 R16 <small>(110)</small>	265/65 R17 <small>(112)</small>	265/60 R18 <small>(110)</small>
RIM SIZE (minimum)	16X7J	17X7.5J	18X8J	16X7J	17X7.5J	18X8J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	260kPa (240kPa)	260kPa (240kPa)	260kPa (240kPa)	300kPa (240kPa)	300kPa (240kPa)	300kPa (240kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1480kg	1480kg	1480kg	2020kg	2020kg	2020kg
(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE. THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "N" (140km/h). THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3500kg						

LS-Ford Ranger and Mazda BT50 TP05

Ph: +61 2 9820 6800

Email: sales@lovells.com.au
www.lovellsauto.com.au

