

NISSAN PATROL Y61 GU 3900KG GVM UPGRADE



Kit #: NISSKIT020-GVM

Capacities	Lovells	OE
GVM	3900kg	3400kg
GCM	6200kg	6200kg
Front Axle	1660kg	
Rear Axle	2240kg	
Towing	3200kg	3200kg

DATES

Trayback Only
3.0 Ltr Only
03/2007 on

SPRING OPTIONS

FRONT: DFS-41 – 0 to 100kg Constant Load

REAR: NP-61 – Only Rear Leaf Spring Available, 0 to 100kg Constant Load
NP-61HD – Only Rear Leaf Spring Available, 150 to 250kg Constant Load

SHOCK PART NUMBERS

FRONT: 64612491 (Twin Tube Shocks)

REAR: 6462525P (Twin Tube Shocks)

OTHER KIT COMPONENTS

Eye & Shackle Bushed
U-Bolts
Greaseable Shackles
Greaseable Pins
Cat 6 Indicators
Tyre Placard
Decals

NOTES:

SVI Plate Location:

State Compliance Only

Lovells Approval Number:

VTA 028971

Tyres:

Factory tyres meet minimum specification

Special Requirements:

CAT6 indicators are required to be compliant
Recommended to fit Front ABS spacer

TYRE – LOADING INFORMATION		
FOR GVM 3900KG	FRONT AXLE	REAR AXLE
TYRE SIZE	265/75R16LT(112)	265/75R16LT(112)
RIM SIZE	16X8.0JJ	16X8.0JJ
RECOMMENDED COLD TYRE INFLATION PRESSURE	250kPa (240kPa)	350kPa (260kPa)
LOAD CARRYING CAPACITY PER AXLE	1660kg	2240kg
() : TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE. THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "L" (120km/h). SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3900kg		

LS-NP1701

Ph: +61 2 9820 6800

Email: sales@lovells.com.au
www.lovellsauto.com.au

