

RAM 1500 DS

3950KG GVM UPGRADE



Kit #: RAMKIT001-GVM

Capacities	Lovells	OE
GVM	3950kg	3450kg
GCM	OE SPEC	OE SPEC
Front Axle	1770kg	
Rear Axle	2180kg	
Towing	OE SPEC	OE SPEC

DATES
07/2020 on

SPRING OPTIONS

FRONT: DFR-150 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1700kg
 DFR-150HD – Load bearing front accessories, including Bullbar. Axle capacities over 1700kg

REAR: DRR-151HD – Axle capacities under 1350kg
 DRR-151EHD – Axle capacities over 1350kg

SHOCK PART NUMBERS

FRONT: 64611050 (Twin Tube Shocks)
REAR: 64611051 (Twin Tube Shocks)

OTHER KIT COMPONENTS

Cat 6 Indicators
 Tyre Placard
 Decals

NOTES:

SVI Plate Location:

Drivers Side A Pillar

Lovells Approval Number:

VTA 051523

Tyres & Rims:

TYRES MUST BE CHANGED TO A MINIMUM LOAD RATING OF 114 & SPEED RATING OF Q RIMS MUST BE AFTERMARKET WITH A LOAD RATING OF 1100KG

Special Requirements:

CAT6 indicators are required to be compliant

TYRE – LOADING INFORMATION			
TYRE SIZE <small>(Tyre Load Index minimum)</small>	RIM SIZE <small>(Minimum Rim Load Rating 1100kg)</small>	FRONT AXLE RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM	REAR AXLE RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM
P175/60R20 (114)	20X9.0J	240kPa (240kPa)	250kPa (240kPa)
P175/60R20 (114)	20X8.0J	240kPa (240kPa)	250kPa (240kPa)
275/60R20 (114)	20X9.0J	240kPa (240kPa)	250kPa (240kPa)
275/60R20 (114)	20X8.5J	240kPa (240kPa)	250kPa (240kPa)
LT285/65R18 (114)	18X9.0J	240kPa (240kPa)	250kPa (240kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)		1770kg	2180kg
(:) TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 250 KGS OR LESS OF LUGGAGE			
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.			
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q" (160km/h).			
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION			
THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 250KG			
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3950kg			

LS_RAM_DS_V2

Ph: +61 2 9820 6800

Email: sales@lovells.com.au
www.lovellsauto.com.au



RAM 1500 DS

3950KG GVM UPGRADE



Kit #: RAMKIT002-GVM-PLAT

Capacities	Lovells	OE
GVM	3950kg	3450kg
GCM	OE SPEC	OE SPEC
Front Axle	1770kg	
Rear Axle	2180kg	
Towing	OE SPEC	OE SPEC

DATES

07/2020 on

SPRING OPTIONS

FRONT: DFR-150 – Minimal load bearing front accessories, including Bullbar. Axle capacities under 1700kg
 DFR-150HD – Load bearing front accessories, including Bullbar. Axle capacities over 1700kg

REAR: DRR-151HD – Axle capacities under 1350kg
 DRR-151EHD – Axle capacities over 1350kg

SHOCK PART NUMBERS

FRONT: 64611050-2.0ADJMONO (Remote Res Shocks)

REAR: 64611051SR-2.0ADJMONO (Remote Res Shocks)
 64611051SL-2.0ADJMONO (Remote Res Shocks)

OTHER KIT COMPONENTS

Cat 6 Indicators
 Tyre Placard
 Decals

NOTES:

SVI Plate Location:

Drivers Side A Pillar

Lovells Approval Number:

VTA 051523

Tyres & Rims:

TYRES MUST BE CHANGED TO A MINIMUM LOAD RATING OF 114 & SPEED RATING OF Q
RIMS MUST BE AFTERMARKET WITH A LOAD RATING OF 1100KG

Special Requirements:

CAT6 indicators are required to be compliant

TYRE – LOADING INFORMATION			
TYRE SIZE <small>(Tyre Load Index minimum)</small>	RIM SIZE <small>(Minimum Rim Load Rating 1100kg)</small>	FRONT AXLE RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM	REAR AXLE RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM
P175/60R20 (114)	20X9.0J	240kPa (240kPa)	250kPa (240kPa)
P175/60R20 (114)	20X8.0J	240kPa (240kPa)	250kPa (240kPa)
275/60R20 (114)	20X9.0J	240kPa (240kPa)	250kPa (240kPa)
275/60R20 (114)	20X8.5J	240kPa (240kPa)	250kPa (240kPa)
LT285/65R18 (114)	18X9.0J	240kPa (240kPa)	250kPa (240kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)		1770kg	2180kg
(:) TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 250 KGS OR LESS OF LUGGAGE			
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.			
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "Q" (160km/h).			
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION			
THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 250KG			
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3950kg			

LS_RAM_DS_V2

Ph: +61 2 9820 6800

Email: sales@lovells.com.au
www.lovellsauto.com.au

