

TOYOTA J7 79 SERIES 3900KG GVM UPGRADE



Kit #: TOYKIT061-GVM-J7

Capacities	Lovells	OE
GVM	3900kg	3510kg
GCM	7400kg	6800kg
Front Axle	1540kg	
Rear Axle	2360kg	
Towing	3500kg	3500kg

<u>DATES</u>
All models 08/2022 on

<u>SPRING OPTIONS</u>	
FRONT:	TFS-79 – Standard Height Coil Spring, 0 to 100kg Constant Load TFR-79 – Raised Height Coil Spring, 100 to 150kg Constant Load TFR-79HD – Raised Height Heavy Duty Coil Spring, 150 to 250kg Constant Load
REAR:	TL-79XHD – Heavy Duty Leaf Spring (11 Leaf), 400 to 500kg Constant Load TL-79SR – Heavy Duty Leaf Spring (12 Leaf), 500 to 600kg Constant Load

<u>SHOCK PART NUMBERS</u>	
FRONT:	64612491 (Twin Tube Shocks)
REAR:	64612492 (Twin Tube Shocks)

<u>OTHER KIT COMPONENTS</u>
Eye & Shackle Bushed
Caster Correction Bushes (Additional fitting time required)
U-Bolts
Greasable Shackles
Greasable Pins
Rear Handbrake Cable Extension Bracket
Tyre Placard
Decals

<u>NOTES:</u>
SVI Plate Location: RHS Firewall
Lovells Approval Number: VTA 061197
Tyres: Factory tyres meet minimum specification
Special Requirements: OE Side indicator is CAT6 compliant

<u>TYRE – LOADING INFORMATION</u>						
	FRONT AXLE			REAR AXLE		
TYRE SIZE (minimum) <small>(Tyre Load Index minimum)</small>	225/95R16 (114)	7.50R16 LT (114)	265/70R16 LT (114)	225/95R16 (114)	7.50R16 LT (114)	265/70R16 LT (114)
RIM SIZE (minimum)	16X6J	16X5.50F	16X7J	16X6J	16X5.50F	16X7J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	250kPa (240kPa)	250kPa (240kPa)	300kPa (250kPa)	475kPa (260kPa)	475kPa (260kPa)	450kPa (250kPa)
LOAD CARRYING CAPACITY PER AXLE <small>(maximum)</small>	1540kg			2360kg		
<small>(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE</small>						
<small>THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.</small>						
<small>THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "L" (120km/h).</small>						
<small>SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG</small>						
<small>THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 3900kg</small>						

LS-LC78/79TP V4 3900

TOYOTA J7 79 SERIES 4200KG GVM UPGRADE

Kit #: TOYKIT080-GVM-J7



Capacities	Lovells	OE
GVM	4200kg	3510kg
GCM	7400kg	6800kg
Front Axle	1650kg	
Rear Axle	2550kg	
Towing	3500kg	3500kg

<u>DATES</u>
All models 08/2022 on

SPRING OPTIONS

FRONT: TFS-79 – Standard Height Coil Spring, 0 to 100kg Constant Load
 TFR-79 – Raised Height Coil Spring, 100 to 150kg Constant Load
 TFR-79HD – Raised Height Heavy Duty Coil Spring, 150 to 250kg Constant Load

REAR: TL-79XHD – Heavy Duty Leaf Spring (11 Leaf), 400 to 500kg Constant Load
 TL-79SR – Heavy Duty Leaf Spring (12 Leaf), 500 to 600kg Constant Load

SHOCK PART NUMBERS

FRONT: 64612491 (Twin Tube Shocks)
 REAR: 64612492 (Twin Tube Shocks)

NOTES:

SVI Plate Location:
RHS Firewall

Lovells Approval Number:
VTA 061197

Tyres:
**TYRES MUST BE CHANGED TO
A MINIMUM LOAD RATING
OF 117 & SPEED RATING OF M**

Special Requirements:
OE Side indicator is CAT6
compliant

OTHER KIT COMPONENTS

Eye & Shackle Bushed
 Caster Correction Bushes (Additional fitting time required)
 U-Bolts
 Greasable Shackles
 Greasable Pins
 Rear Handbrake Cable Extension Bracket
 Tyre Placard
 Decals

TYRE – LOADING INFORMATION						
	FRONT AXLE			REAR AXLE		
TYRE SIZE (minimum) <small>(Tyre Load Index minimum)</small>	225/95R16 (117)	7.50R16 LT (117)	265/70R16 LT (117)	225/95R16 (117)	7.50R16 LT (117)	265/70R16 LT (117)
RIM SIZE (minimum)	16X6J	16X5.50F	16X7J	16X6J	16X5.50F	16X7J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	250kPa (240kPa)	250kPa (240kPa)	300kPa (250kPa)	475kPa (260kPa)	475kPa (260kPa)	450kPa (250kPa)
LOAD CARRYING CAPACITY PER AXLE <small>(maximum)</small>	1650kg			2550kg		
<small>(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE</small>						
<small>THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.</small>						
<small>THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "M" (130km/h).</small>						
<small>SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG</small>						
<small>THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 4200kg</small>						

LS-LC79ANCAPTP V3 4200

TOYOTA J7 79 SERIES 4200KG GVM UPGRADE

Kit #: TOYKIT080-GVM-PLAT-J7



Capacities	Lovells	OE
GVM	4200kg	3510kg
GCM	7400kg	6800kg
Front Axle	1650kg	
Rear Axle	2550kg	
Towing	3500kg	3500kg

DATES
All models 08/2022 on

SPRING OPTIONS	
FRONT:	TFS-79 – Standard Height Coil Spring, 0 to 100kg Constant Load TFR-79 – Raised Height Coil Spring, 100 to 150kg Constant Load TFR-79HD – Raised Height Heavy Duty Coil Spring, 150 to 250kg Constant Load
REAR:	TL-79XHD – Heavy Duty Leaf Spring (11 Leaf), 400 to 500kg Constant Load TL-79SR – Heavy Duty Leaf Spring (12 Leaf), 500 to 600kg Constant Load

SHOCK PART NUMBERS	
FRONT:	64612491-2.0ADJMONO (Remote Res Shocks)
REAR:	64612492-2.0ADJMONO (Remote Res Shocks)

OTHER KIT COMPONENTS
Eye & Shackle Bushed Caster Correction Bushes (Additional fitting time required) U-Bolts Greaseable Shackles Greaseable Pins Rear H/brake Cable Extension Bracket Tyre Placard Decals

NOTES:
SVI Plate Location: RHS Firewall
Lovells Approval Number: VTA 061197
Tyres: TYRES MUST BE CHANGED TO A MINIMUM LOAD RATING OF 117 & SPEED RATING OF M
Special Requirements: OE Side indicator is CAT6 compliant

TYRE – LOADING INFORMATION						
	FRONT AXLE			REAR AXLE		
TYRE SIZE (minimum) <small>(Tyre Load Index minimum)</small>	225/95R16 (117)	7.50R16 LT (117)	265/70R16 LT (117)	225/95R16 (117)	7.50R16 LT (117)	265/70R16 LT (117)
RIM SIZE (minimum)	16X6J	16X5.50F	16X7J	16X6J	16X5.50F	16X7J
RECOMMENDED COLD TYRE INFLATION PRESSURE - At maximum GVM - (No Load)	250kPa (240kPa)	250kPa (240kPa)	300kPa (250kPa)	475kPa (260kPa)	475kPa (260kPa)	450kPa (250kPa)
LOAD CARRYING CAPACITY PER AXLE (maximum)	1650kg			2550kg		
(): TYRE PRESSURE WITH 2 OR LESS OCCUPANTS AND 500 KGS OR LESS OF LUGGAGE						
THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THIS VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD SHOWN ABOVE.						
THE TYRE FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY NOT LESS THAN "M" (130km/h).						
SEE FITTING INSTRUCTIONS FOR ADDITIONAL INFORMATION THIS GVM UPGRADE IS RECOMMENDED FOR A CONSTANT PAYLOAD OF 400KG						
THIS VEHICLE IS FITTED WITH A LOVELLS GVM UPGRADE THE GVM OF THIS VEHICLE MUST NOT EXCEED 4200kg						

LS-LC79ANCAPTP V3 4200